

Animo Water boilers

Animo water boilers

Hot water is not only used for coffee or tea. For instance, instant products like soup and hot chocolate are being consumed more often. When large quantities of hot water are needed in a short time, the high-quality Animo machines are really convenient.

The Animo ComBi-line combines the supply of hot water with a coffee-making machine (see pages 4 - 7). Additionally, Animo offers various other options.



WKI-series



WKT-series

The WKI-series: wall-mounted

With a WKI-series storage water boiler you always have hot water. You tap exactly the quantity of water without the temperature decreasing. Their high speed and flexibility make the WKI ideal for professional use. WKI water boilers have a fixed water connection. The adjustable thermostat keeps the water at a constant temperature. After having withdrawn water, the WKI refills quickly. WKI boilers are available with a swivel arm tap. A no-drip tap is optional. Options: 10, 20, 40, 60 or 80 litres.

The WKT-series: buffet model

All WKT-series storage water boilers are counter models. They are single walled as standard and have a thermostat and dry-boil protection. This range has a gauge glass and a no-drip tap. They are available with a fixed water connection (VA) or for manual filling (HA). Options: 10 or 20 litres.

The WKT-D-series: double walled

WKT-D storage water boilers have a double walled, stainless steel housing. The safe polyurethane insulation prevents the outside from becoming hot. The lid has been insulated as well. The WKT-D water boilers have a gauge glass, a non-drip tap and an adjustable thermostat as standard. Available in 5, 10 and 20 litre models, with (VA) or without (HA) fixed water connection, they are a perfect combination with the ComBi-line coffee-making machines.

WKT-3n: with drip tray

The WKT-3n is a double walled water boiler. It is equipped as standard with a drip tray. Available with (VA) or without a (HA) fixed water connection. The WKT-3n can easily be combined with Animo's M-line (jug machines).



Animo Water boilers



*More and more instant products
like soup and hot chocolate are being consumed.*

Daalderop 5HWA

This original Daalderop water boiler heats up 2.5 litres of water in only 7 minutes. The counter model has a storage capacity of 5 litres and has an insulated grip, gauge glass and no-drip tap. The Daalderop 5HWA is a full part of the Animo range, but it has retained its own design.

WKS: with steam tap

The WKS water boiler not only has a hot water tap, it has a steam tap as well. The steam is used for heating milk or chocolate. The hot water tap is particularly suitable for tapping small quantities of hot water (cups). The WKS has a capacity of 25 litres per hour.

A special descaling agent for cleaning water boilers is available from Animo in sachets or wholesale packs.



ANIMO ANYWAY

Animo equipment is a sensible investment in every way. The stainless steel housing is not only indestructible, it can also be completely recycled. The other components are made of high-quality materials and are very durable. Furthermore, Animo pays a great deal of attention to the use of energy. The double walled systems are strongly heat-insulating. All energy ends up in a nice, hot cup of coffee or tea. And this gives renewed energy!

Animo Beverage containers

Animo beverage containers

In practice there may be some time between making and serving hot or cold beverages. In particular when large quantities are involved. For retaining the taste and quality it is important that the beverages are kept at the right temperature. Animo beverage containers are ideal for professional use in for example hospitals, staff restaurants, sports canteens and event catering. They are available in various models. When making your choice, two questions are important:

Do you want an electrically heated container or not?

When the containers are always used at a place where electricity is available, the electrical model is best. A small heating element maintains the beverage at the perfect temperature. However, when the containers are used at different locations or under unpredictable conditions, insulated containers are a better choice. A double walled stainless steel housing with a polyurethane insulation layer makes sure that the beverages remain at the original temperature for a long time. Besides, insulated containers save energy.

Do you want a 4, 5, 6, 8, 10, 12, 16, 20 or 25 litre container?

This choice will largely depend on the capacity required. However, the size of your biceps may be of interest too. In fact, small containers are easier to move. Besides, several smaller containers give more flexibility than one large container. By the way, containers of the same size can be stacked. Whatever you need, Animo has the right capacity for you.



CN-series: part of the ComBi-line, but also separately available and usable. Transportable, stackable, with integrated gauge glass and no-drip tap. Electrical (CNe) or insulated (CNi) model. Options: 5, 10 or 20 litres.

Animo Beverage containers



CE-series: equipped with a heating element with klixon thermostat that does not touch the bottom. This gives a hot air au bain-marie effect that maintains the proper temperature of the beverage (about 85 °C) and it can be kept for a longer time. Options: 4, 6, 8, 10, 12, 16, 20 or 25 litres. 4 - 8 litre containers have a carrying bracket, the others have grips.



Option: Clip on lid,
Tap-protecting bracket

CI-series: suitable for hot and cold beverages. The polyurethane insulation maintains the beverage at a constant temperature for a very long time. Options: 4, 6, 8, 10, 12, 16, 20 or 25 litres. 4 - 8 litre containers have a carrying bracket, the others have grips.

When you serve nice, hot beverages, you will also receive warm reactions.



Animo Water boilers - Specifications

ComBi-line

	CB 5	CB 5W	CB 10	CB 10W	CB 20	CB 20W
Article number	10630	10635	10670	10675	10710	10715
Hour capacity hot water	abt. 30 l	abt. 30 l	abt. 60 l	abt. 60 l	abt. 90 l	abt. 90 l
Buffer stock hot water (W)	-	4,2 l	-	5,6 l	-	5,6 l
Hour capacity hot water (W)	-	22 l	-	22 l	-	22 l
Water dispensing in 1 run	-	2,2 l	-	3,6 l	-	3,6 l
Electrical connection	1N~220-240V, 3200W, 50-60Cy	3N~380-415V, 5400W, 50-60Cy	3N~380-415V, 6200W, 50-60Cy	3N~380-415V, 8400W, 50-60Cy	3N~380-415V, 9200W, 50-60Cy	3N~380-415V, 11400W, 50-60Cy
Water connection	yes	yes	yes	yes	yes	yes
Dimensions (WxDxH)	235 x 345 x 707 mm	235 x 490 x 707 mm	235 x 345 x 800 mm	235 x 490 x 800 mm	235 x 345 x 901 mm	235 x 490 x 901 mm
Water dosing time	abt. 10 min/5 l	abt. 10 min/5 l	abt. 10 min/10 l	abt. 10 min/10 l	abt. 14 min/20 l	abt. 14 min/20 l
Suitable for	CN5e/i	CN5e/i	CN10e/i	CN10e/i	CN20e/i	CN20e/i

WKI-n

	WKI 10n	WKI 20n 3kW	WKI 20n 6kW	WKI 40n	WKI 60n	WKI 80n
Article number	30110	30115	30120	30125	30130	30135
Buffer stock hot water	10 l	20 l	20 l	40 l	60 l	80 l
Hour capacity hot water	30 l	30 l	60 l	90 l	90 l	180 l
Electrical connection	1N~220-240V, 3200W, 50-60Cy	1N~220-240V, 3200W, 50-60Cy	3N~380-415V, 6600W, 50-60Cy	3N~380-415V, 9600W, 50-60Cy	3N~380-415V, 9600W, 50-60Cy	3N~380-415V, 19200W, 50-60Cy
Water connection	yes	yes	yes	yes	yes	yes
Dimensions Ø x H	224 x 520 mm	304 x 580 mm	304 x 580 mm	385 x 685 mm	385 x 855 mm	445 x 890 mm
Holding temperature	adjustable upto 97°C					
Heating time	20 -> 97°C: 17 min	20 -> 97°C: 34 min	20 -> 97°C: 17 min	20 -> 97°C: 23 min	20 -> 97°C: 35 min	20 -> 97°C: 25 min
Tapping speed	6-9 sec/l					



WKT-n

	WKT 10n HA	WKT 10n VA	WKT 20n HA	WKT 20nVA	WKT 3n HA	WKT 3n VA
Article number	30145	30140	30155	30150	30100	30101
Buffer stock hot water	10 l	10 l	20 l	20 l	3 l	3 l
Water dispensing in 1 run	8 l	8 l	18 l	18 l	2 l	2 l
Hour capacity hot water	30 l	30 l	30 l	30 l	21 l	21 l
Electrical connection	1N~220-240V, 3200W, 50-60Cy	1N~220-240V, 3200W, 50-60Cy	1N~220-240V, 3200W, 50-60Cy	1N~220-240V, 3200W, 50-60Cy	1N~220-240V, 2100W, 50-60Cy	1N~220-240V, 2100W, 50-60Cy
Water connection	no	yes	no	yes	no	yes
Dimensions Ø x H	225 x 505 mm	225 x 505 mm	305 x 560 mm	305 x 560 mm	215(W) x 280(D) x 445(H)	215(W) x 280(D) x 445(H)
Holding temperature	adjustable upto 97°C					
Heating time	20 -> 97°C: 17 min	20 -> 97°C: 17 min	21 -> 97°C: 34 min	21 -> 97°C: 34 min	20 -> 90°C: 8 min	20 -> 90°C: 8 min

WKT-Dn

	WKT-D 5n HA	WKT-D 5n VA	WKT-D 10n HA	WKT-D 10n VA	WKT-D 20n HA	WKT-D 20n VA
Article number	30040	30055	30045	30060	30050	30065
Buffer stock hot water	5 l	5 l	10 l	10 l	20 l	20 l
Water dispensing in 1 run	4 l	4 l	8 l	8 l	18 l	18 l
Hour capacity hot water	30 l					
Electrical connection	1N~220-240V, 3200W, 50-60 Cy					
Water connection	no	yes	no	yes	no	yes
Dimensions Ø x H	237 x 406 mm	237 x 406 mm	307 x 427 mm	307 x 427 mm	355 x 515 mm	355 x 515 mm
Holding temperature	adjustable upto 97°C					
Heating time	20 -> 97°C: 9 min	21 -> 97°C: 9 min	22 -> 97°C: 17 min	23 -> 97°C: 17 min	24 -> 97°C: 34 min	25 -> 97°C: 34 min

WKS

	WKS
Article number	30037
Contents steambosiler	3,5 l
Buffer stock hot water	3 l
Hour capacity hot water	25 l
Hour capacity steam	25 l
Electrical connection	1N~220-240V, 3200W, 50-60 Cy
Water connection	yes
Dimensions (WxDxH)	195 x 490 x 465 mm
Heating time	ca. 9 min

Animo Beverage containers - Specifications

Beverage containers CE/CI

	CE 4	CE 6	CE 8	CE 10	CE 12	CE 16	CE 20	CE 25
Article number	50050	50051	50052	50053	50054	50055	50056	50057
Contents	4 l, 32 cups	6 l, 48 cups	8 l, 64 cups	10 l, 80 cups	12 l, 96 cups	16 l, 128 cups	20 l, 160 cups	25 l, 200 cups
Electrical connection	1N-220-240V, 165W, 50-60 Cy	1N-220-240V, 165W, 50-60 Cy	1N-220-240V, 165W, 50-60 Cy	1N-220-240V, 165W, 50-60 Cy	1N-220-240V, 275W, 50-60 Cy	1N-220-240V, 275W, 50-60 Cy	1N-220-240V, 385W, 50-60 Cy	1N-220-240V, 385W, 50-60 Cy
Dimensions Ø x H	237 x 346 mm	237 x 405 mm	252 x 436 mm	252 x 489 mm	307 x 427 mm	307 x 504 mm	307 x 576 mm	307 x 655 mm
Weight	4,9 kg	5,5 kg	6,1 kg	6,7 kg	8,3 kg	9,5 kg	10,5 kg	11,5 kg
Holding temperature	abt. 84-86°C							
Tap height	120 mm							

	CI 4	CI 6	CI 8	CI 10	CI 12	CI 16	CI 20	CI 25
Article number	50038	50039	50040	50041	50042	50043	50044	50045
Contents	4 l, 32 cups	6 l, 48 cups	8 l, 64 cups	10 l, 80 cups	12 l, 96 cups	16 l, 128 cups	20 l, 160 cups	25 l, 200 cups
Dimensions Ø x H	237 x 346 mm	237 x 405 mm	252 x 436 mm	252 x 489 mm	307 x 427 mm	307 x 504 mm	307 x 576 mm	307 x 655 mm
Weight	4,5 kg	5,1 kg	5,9 kg	6,5 kg	8 kg	9,2 kg	10,3 kg	11,2 kg
Temperature loss per hour	5°C	4°C	4°C	3°C	3°C	3°C	3°C	3°C
Isolation	Polyurethane CFK-free							
Tap height	120 mm							

Beverage containers CN

	CN5e	CN10e	CN20e	CN5i	CN10i	CN20i
Article number	51105 / 51155 *	51110 / 51160 *	51120 / 51170 *	51205 / 51255 *	51210 / 51260 *	51220 / 51270 *
Contents	5 l	10 l	20 l	5 l	10 l	20 l
Electrical connection	1N-220-240V, 35W, 50-60Hz	1N-220-240V, 70W, 50-60Hz	1N-220-240V, 70W, 50-60Hz	-	-	-
Dimensions Ø x H	237 x 406 mm	307 x 427 mm	355 x 515 mm	237 x 406 mm	307 x 427 mm	355 x 515 mm
Weight	5,1 kg	7,3 kg	11,2 kg	5 kg	7,2 kg	11 kg
Tap height	120 mm	120 mm	120 mm	120 mm	120 mm	120 mm
Temperature loss per hour	-	-	-	4°C	3°C	2,5°C
Holding temperature	abt. 80-85°C	abt. 80-85°C	abt. 80-85°C	-	-	-

* Container without gauge glass

Options and accessories: tap protection (art.no. 99748), clip on lid (art. no. 99747), S-swivel arm (art.no. 99497) and container tube with tap (art.no. 99499)

