



Elbow connector M1/2" threaded with check valve (comp. EN 1717)
 Thermoplastic anti-friction rollers against hose wear and tear.
 Retractable hose (15 m. long) with an internal rubber mixture in EPDM and coated with a blue protection sheet. This material is in accordance with FDA specifications required for Drinking Water.
 Protection spring in stainless steel
 Spray-gun mod. "Nito-2 COMBI" with connection F 1/2"

Casing and mounting frame in stainless steel AISI 304 fine glazed.
 Possibility to regulate the loading of the retraction spring.
 The Hose Reel is swinging, this reduces the wear and tear of the hose and helps its pulling out.

SPRAY GUN NITO II COMBI
"Heavy Duty Gun" for industrial cleaning.
Used for flushing and cleaning jobs in industries requiring a sturdy gun, that saves water when in use.

- Infinitely variable: from a concentrated jet to a spray with a dispersion angle of 60 degrees
- Easy regulation of the nozzle
- For safety reasons the gun can be locked, in order to avoid unintentional water jets.
- Thermic protection of the hand
- Ergonomically correct design (weight: 0,7 Kg)



OPERATING BENCHMARKS:
By constant flow:
 Water temperature 60°C by 6 bar pressure (min. pressure: 2,5 bar)
Peaks:
 Water pressure max. 10 bar by water temperature < 60°C
 Water temperature max. 90°C by water pressure < 6 bar
 Water Output of the Spray Gun only: 40 l/min. (at 5 bar)

5R.M15.449 "MAXIReel" with automatic retraction system (hose L. 15 m.) and NITO-2 Spray-gun F 1/2"